

UT325 contact type thermometer provide fast, accurate, and precise temperature measurement with thermocouple temperature probes. Users can select single or dual input, record, and analyze data through PC software. UT325 can be used with a variety of temperature probes, satisfying multiple applications.



UT325

Specifications	Range	Accuracy
<b>Certificates</b>	<b>CE, UKCA</b>	
Single or dual input	Dual	
Temperature probe type	Type K	-200°C~1372°C (-328°F~2501°F)
	Type J	-210°C~1200°C (-346°F~2192°F)
	Type T	-250°C~400°C (-418°F~752°F)
	Type E	-150°C~1000°C (-238°F~1832°F)
	Type R	0°C~1767°C (32°F~3212°F)
	Type S	0°C~1767°C (32°F~3212°F)
	Type N	-200°C~1300°C (-328°F~2372°F)
Resolution	0.1°C (When value>999.9°C: 1°C)	
Data storage	100	
High/low alarm	√	
High/low signal output	√	

Features	
°C/°F/K selection	MAX/MIN/AVG mode
Data hold	USB interface
Auto power off	LCD backlight alarm
Low battery indication	Auto calibration

Characteristics	
Standard accessories	Battery, USB interface cable, K-type temperature probe, English manual
Power	USB or 9V battery (6F22)
Display	30 x 32mm
Product size	175 x 85 x 30mm
Product net weight	270g
Standard individual packing	Gift box
Standard quantity per carton	10pcs
Standard carton measurement	405 x 290 x 165mm
Standard carton gross weight	4.3kg